

Panel Cubicles – K32

Product Reference: Rearo Rapidfit MFC Cubicles

Manufacturer: Rearo Laminates
Address: 29 Loanbank Quadrant, Glasgow G51 3HZ
T: 0141 440 0800
E: commercial@rearo.co.uk
Web: www.rearo.co.uk/commercial

Panels:

- Height (overall): Standard 1950mm FFL.
- Floor Clearance: 150mm.
- Depth: Standard 1500mm
- Core material: Moisture Resistant Melamine-Faced Chipboard (MR MFC).
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: All edges square and lipped with 2mm PVC edging.
- Wall Support: Nickel Powder Coated Aluminium U – Channel brackets with bolt through fixings

Pilasters:

- Panel Height: 1800mm.
- Core material: Moisture Resistant Melamine-Faced Chipboard (MR MFC).
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: All edges square and lipped with 2mm PVC edging.
- Ironmongery: Nickel Powder Coated Aluminium U – Channel brackets with bolt through fixings

Doors:

- Panel Height: 1800mm.
- Core material: Moisture Resistant Melamine-Faced Chipboard (MR MFC) Pre-drilled to suit Hinge and Indicator bolt positions.
- Thickness: 19mm.
- Colour: From the Rearo Rapidfit colour chart.
- Edge treatment: All edges square and lipped with 2mm PVC edging.
- Ironmongery: Indicator Bolt - Coin operated emergency release including keeper with concealed fixings.
Hinges - Nickel Powder Coated Aluminium butt hinges with nylon cams to set closed door position. Coat
Hook: Nickel Powder Coated Aluminium coat hook with buffer.

Fittings:

- Headrail: Nickel Powder Coated Aluminium.
- Legs: 150mm high Nickel Powder Coated Aluminium adjustable legs.

Accessories:

- Headrail End Caps: Nickel Powder Coated Aluminium, to suit corner sited / free standing cubicles.
- Outward Opening Keeper: Nickel Powder Coated Aluminium, to suit outward opening doors.

INSTALLATION

- *Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.*
- *Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.*
- *Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.*
- *Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.*
- *Moisture and thermal movement: Make adequate allowance for future movement.*